

CODES AND PREFERRED NUMBERS FOR FIXED RESISTORS



COLOR	1ST BAND ●	2ND BAND ●	3RD BAND	● MULTIPLIER	● TOLERANCE
BLACK	0	0	0	1Ω	
BROWN	1	1	1	10Ω	± 1% (F)
RED	2	2	2	100Ω	± 2% (G)
ORANGE	3	3	3	1KΩ	
YELLOW	4	4	4	10KΩ	
GREEN	5	5	5	100KΩ	± 0.5% (D)
BLUE	6	6	6	1MΩ	± 0.25% (C)
VIOLET	7	7	7	10MΩ	± 0.10% (B)
GREY	8	8	8		± 0.05%
WHITE	9	9	9		
GOLD				0.1	± 5% (J)
SILVER				0.01	± 10% (K)

■ STANDARD RESISTANCE VALUES FOR THE 10-TO-100 DECADE (Also usable in decade multiples or sub-multiples)

RESISTANCE TOLERANCE (± %)																	
0.1% 0.25% 0.5%	1%	2% 5% 10%	0.1% 0.25% 0.5%	1%	2% 5% 10%	0.1% 0.25% 0.5%	1%	2% 5% 10%	0.1% 0.25% 0.5%	1%	2% 5% 10%	0.1% 0.25% 0.5%	1%	2% 5% 10%	0.1% 0.25% 0.5%	1%	2% 5% 10%
10.0	10.0	10	14.7	14.7	-	21.5	21.5	-	31.6	31.6	-	46.4	46.4	-	68.1	68.1	68
10.1	-	-	14.9	-	-	21.8	-	-	32.0	-	-	47.0	-	47	69.0	-	-
10.2	10.2	-	15.0	15.0	15	22.1	22.1	22	32.4	32.4	-	47.5	47.5	-	69.8	69.8	-
10.4	-	-	15.2	-	-	22.3	-	-	32.8	-	-	48.1	-	-	70.6	-	-
10.5	10.5	-	15.4	15.4	-	22.6	22.6	-	33.2	33.2	33	48.7	48.7	-	71.5	71.5	-
10.6	-	-	15.6	-	-	22.9	-	-	33.6	-	-	49.3	-	-	72.3	-	-
10.7	10.7	-	15.8	15.8	-	23.2	23.2	-	34.0	34.0	-	49.9	49.9	-	73.2	72.3	-
10.9	-	-	16.0	-	16	23.4	-	-	34.4	-	-	50.5	-	-	74.1	-	-
11.0	11.0	11	16.2	16.2	-	23.7	23.7	-	34.8	34.8	-	51.1	51.1	51	75.0	75.0	75
11.1	-	-	16.4	-	-	24.0	-	24	35.2	-	-	51.7	-	-	75.9	-	-
11.3	11.3	-	16.5	16.5	-	24.3	24.3	-	35.7	35.7	-	52.3	52.3	-	76.8	76.8	-
11.4	-	-	16.7	-	-	24.6	-	-	36.1	-	36	53.0	-	-	77.7	-	-
11.5	11.5	-	16.9	16.9	-	24.9	24.9	-	36.5	36.5	-	53.6	53.6	-	78.7	78.7	-
11.7	-	-	17.2	-	-	25.2	-	-	37.0	-	-	54.2	-	-	79.6	-	-
11.8	11.8	-	17.4	17.4	-	25.5	25.5	-	37.4	37.4	-	54.9	54.9	-	80.6	80.6	-
12.0	-	12	17.6	-	-	25.8	-	-	37.9	-	-	55.6	-	-	81.6	-	-
12.1	12.1	-	17.8	17.8	-	26.1	26.1	-	38.3	38.3	-	56.2	56.2	56	82.5	82.5	82
12.3	-	-	18.0	-	18	26.4	-	-	38.8	-	-	56.9	-	-	83.5	-	-
12.4	12.4	-	18.2	18.2	-	26.7	26.7	-	39.2	39.2	39	57.6	57.6	-	84.5	84.5	-
12.6	-	-	18.4	-	-	27.1	-	27	39.7	-	-	58.3	-	-	85.6	-	-
12.7	12.7	-	18.7	18.7	-	27.4	27.4	-	40.2	40.2	-	59.0	59.0	-	86.6	86.6	-
12.9	-	-	18.9	-	-	27.7	-	-	40.7	-	-	57.7	-	-	87.6	-	-
13.0	13.0	13	19.1	19.1	-	28.0	28.0	-	41.2	41.2	-	60.4	60.4	-	88.7	88.7	-
13.2	-	-	19.3	-	-	28.4	-	-	41.7	-	-	61.2	-	-	89.8	-	-
13.3	13.3	-	19.6	19.6	-	28.7	28.7	-	42.2	42.2	-	61.9	61.9	62	90.9	90.9	91
13.5	-	-	19.8	-	-	29.1	-	-	42.7	-	-	62.6	-	-	92.0	-	-
13.7	13.7	-	20.0	20.0	-	29.4	29.4	-	43.2	43.2	43	63.4	63.4	-	93.1	93.1	-
13.87	-	-	20.3	-	-	29.8	-	-	43.7	-	-	64.2	-	-	94.2	-	-
14.0	14.0	-	20.5	20.5	-	30.1	30.1	30	44.2	44.2	-	64.9	64.9	-	95.3	95.3	-
14.2	-	-	20.8	-	-	30.5	-	-	44.8	-	-	65.7	-	-	96.5	-	-
14.3	14.3	-	21.0	21.0	-	30.9	30.9	-	45.3	45.3	-	66.5	66.5	-	97.6	97.6	-
14.5	-	-	21.3	-	-	31.2	-	-	45.9	-	-	67.3	-	-	98.8	-	-
E-192	E-96	E-24	E-192	E-96	E-24	E-192	E-96	E-24	E-192	E-96	E-24	E-192	E-96	E-24	E-192	E-96	E-24